

#### Connect the cable port



Connect the device's coax CABLE connector to a cable outlet in your home.



## Access LAN for initial configuration



To complete initial setup, your CODA will launch Easy Connect user interface on the first connected device. You can access it using a laptop connected by a Ethernet cable or any mobile device with the default Wi-Fi network name/password found on the back label of your new CODA.

Ethernet Method

Wi-Fi Method





## Wireless devices (optional)



You can now connect your wireless devices with the correct SSID and Passphrase chosen in Step 5.

OPTIONAL: To connect a wireless device with the Wi-Fi Protected Setup button (WPS),

You need to first access the GUI with the user "cusadmin" and your Wi-Fi Passphrase as password, enter the Wireless page to enable WPS and set Encrypt Mode to AES then

save the changes. Press the WPS button on the CODA and on the device you wish to connect. You will have 2 minutes to complete the pairing process.



Note: Battery port is used for communication to a Hitron battery backup unit (Optional). Do not use for any other

Connect the power adapter

Connect the included power adapter from

the POWER port to a wall outlet.





purpose.

For initial setup, click "LET'S GO" to test your connection and enter your preferred SSID and Passphrase. The Wi-Fi Passphrase will also act as your administrator password (log with username "cusadmin" the next time you visit 192.168.0.1). Make sure to complete the Easy Connect walk-through so it does not come back. Note: If the CODA receives a factory reset request, the Easy Connect interface will appear again.



# Need Assistance?

You can find additional self-help resources at <u>wavedirect.net/modem</u>

> Contact our Tech Support team at 519-737-9283 Option 2